

BALL COLLECTOR FOR CLEANING SYSTEMS USED FOR FLUID CONDUCTING TUBING

CROSS REFERENCE: Provisional Patent application 60/251,806, filed 12/08/2000

Background of the Invention

This invention relates to cleaning systems which use balls made up of spongy material for cleaning fluid conducting tubing. More specifically it relates to ball collectors in the cleaning systems which includes balls made up of spongy material, the balls having a diameter which is slightly larger than the diameter of the tubing. The ball collector is comprised of a cylindrical housing which has inlet and outlet ports, the latter containing a strainer screen which retains the balls while allowing the fluid to pass through, thereby trapping the balls within the housing, and an access port for retrieving the balls, the access having a removal cover which is transparent. This allows the viewing of the interior of the housing to determine whether any cleaning balls have been trapped within the housing without removing the cover.

Objects of the Invention

This invention relates to cleaning systems which use balls made of spongy material for cleaning fluid conducting tubing. It consists of a ball collector having a housing with inlet and outlet ports, the outlet port having a strainer screen which allows fluid but not the balls to pass, and an access port with a releasable cover. The cover is transparent, preferably having a pyrex glass member encased in a metal sleeve.

An object of the invention is to provide a ball collector for collecting spongy cleaning balls used in cleaning fluid conducting tubing. More specifically, an object is to provide an improved ball collector with a transparent lid to permit the viewing of the interior of the collector for the presence of sediment and cleaning balls without having to remove the lid.

Another object of this invention is to provide a ball collection for collecting cleaning bodies used in cleaning a tubular fluid conducting systems, which is capable of collecting cleaning cleaning bodies without clogging the outlet opening of the collector with foreign matter even when large amounts of foreign matter is introduced into the collector.

Another object of this invention is to provide for a ball collector which does not leak.

These and other objects will be apparent from the disclosures of this invention.

Brief Description of the Figures

Fig. 1. is a cross sectional schematic side view of the ball collector of this invention in place in a fluid drain line.

Fig. 2. is a perspective view of the underside of the hinged cover of this invention.

Fig. 3 is a top perspective view of the cylindrical housing of this invention.

Fig. 4. is a fragmented top perspective view of the ball collector of this invention.

Detailed Description of the Invention

This invention relates to cleaning systems which use balls under fluid pressure to clean fluid conducting tubing. The cleaning system comprises balls (not shown) made up of spongy material with a diameter which is slightly larger than the diameter of the tubing which is being cleaned. The balls are propelled through the tubing by fluid under pressure. The use of these kinds of balls in cleaning systems is well known and need not be described.

Referring to Fig. 1, which is a schematic representation of this invention, the ball collector 1, which is located in the fluid drain lines 2 of the fluid conducting tubing (not shown), of this invention comprises a cylindrical housing 6 which has a bottom 15, an inlet port 8, an outlet port 10 with a strainer screen 28 and an access port 11 which is covered by a lid 14. The arrows in Fig. 1 indicate the direction of flow of cleaning fluid in operation. Referring to Fig. 2 and Fig. 4 the lid 14 comprises a hinged element 22 with a centered access opening 13, and a sleeve element 17 and a transparent cover element 16 encased by the sleeve element 17 and means to attach 48 to the housing 6. The hinged element is countersunk at the periphery of the access opening 13 to form a ledge 44. The transparent cover element 16 and sleeve element 17 are held in place over the access port 11 by countersunk recess of the hinged element 22. The transparent element 16 allows for the viewing of the interior of the housing 6 for the presence of cleaning balls when the lid 14 is locked in place.

Referring to Fig. 2 the hinged cover 22 is substantially rectangular in shape. It is hinged at one side 41 and at the opposite side 42 of the hinged cover 22 is a slot 43 capable of releasably receiving a latch 46 shown in Fig. 4. The latch may be locked in place with a wing nut 47. In a preferred embodiment the cover has an access opening 13. The cover 22 is countersunk on its